



VKECBST Economy Box Sealing Tape

Backing : Biaxially Oriented Polypropylene

Adhesive : Emulsion Pressure Sensitive Water Based Acrylic

Total Thickness	45 μ
Film Thickness	25 μ
Adhesive Thickness	20 μ
180° Peel Adhesion (ASTM D 3330)*	520g/in
Holding Power (ASTM D 3654)*	10 min
Tensile Strength (ASTM D 3759)*	14kg/mm ²
Elongation (ASTM D 3759)*	110%
Initial Tack (JIS Z0237)	<50 mm

Total Thickness Allowance : ± 2 microns.

*Data represents the minimum value from the results of a series of tests.

Storage Conditions: Store in a clean dry place. Temperature of 25°C \pm 2°C and 55% \pm 5% relative humidity is recommended.

Safety / Environmental Information :

MSDS Class:	S	Hazard Ratings:
Health:	1	0. Minimal
Fire:	0	1. Slight
Reactivity:	0	2. Moderate
VOC:	N/A	3. Serious
CONEG:	Complies	4. Extreme

Does not contain any substances according to the Ozone Depleting Substances, 40 CFR Part 82 and the Safe Drinking Water and Toxic Enforcement Act of 1986.

All properties are approximate and are based on tests believed to be reliable and performed in conformance with recommended test methods. These values are presented for comparison purposes and do not represent a guarantee by the manufacturer. It is suggested that purchasers should test, prior to use, the suitability of this product for their particular application.